

Biosorption of nickel ions Ni2+ by natural and modified Pinus caribaea Morelet sawdust

Cynthia Sinyeue, Théophile Garioud, Monika Lemestre, Michaël Meyer,

Frédérique Brégier, Vincent Chaleix, Vincent Sol, Nicolas Lebouvier

► To cite this version:

Cynthia Sinyeue, Théophile Garioud, Monika Lemestre, Michaël Meyer, Frédérique Brégier, et al.. Biosorption of nickel ions Ni2+ by natural and modified Pinus caribaea Morelet sawdust. Heliyon, 2022, 8 (2), pp.e08842. 10.1016/j.heliyon.2022.e08842 . hal-03563781

HAL Id: hal-03563781 https://unc.hal.science/hal-03563781v1

Submitted on 22 Jul 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution - NonCommercial 4.0 International License

Biosorption of nickel ions Ni²⁺ by natural and modified *Pinus caribaea* Morelet sawdust

- 3
- 4 Cynthia Sinyeue^{a,b}, Théophile Garioud^a, Monika Lemestre^a, Michaël Meyer^a, Frédérique
- 5 Brégier^b, Vincent Chaleix^b, Vincent Sol^b, Nicolas Lebouvier^{a*}
- 6
- a: ISEA, EA7484, Université de la Nouvelle Calédonie, Campus de Nouville, 98851
 Nouméa, New Caledonia.
- 9 b: Laboratoire Peirene, EA 7500, Université de Limoges, 87000 Limoges, France
- 10 *Corresponding author: nicolas.lebouvier@univ-nc.nc, Nicolas Lebouvier, ISEA,
- 11 EA7484, Université de la Nouvelle Calédonie, Campus de Nouville, 98851 Nouméa,
- 12 New Caledonia.
- 13


14 Highlights

- 15 *Pinus caribaea* sawdust is an effective biosorbent of metallic trace elements.
- 16 High Ni²⁺ removal efficiency was observed at pH 8 with 5g/L of biosorbent.
- 17 Equilibrium adsorption was described by Freundlich and Langmuir isotherms.
- 18 Pine sawdust is a reusable biosorbent with good desorption capacity.
- 19 Efficiency of acidified and oxidized adsorbents.
- 20

21 Abstract

The potential of *Pinus caribaea* Morelet sawdust for the removal of nickel ions (Ni²⁺) 22 and other metallic trace ions (Co²⁺, Cr³⁺, Mn²⁺) from aqueous solutions was investigated 23 under batch conditions. Several parameters such as size of particles, contact time, pH, 24 initial metal and biomass concentrations, desorption conditions and reusability were 25 evaluated on natural biomass. Biosorption was fast, effective (73%) and biomaterial can 26 be reused after five cycles. To enhance the removal capacity of nickel, pine sawdust was 27 modified by acidic and oxidative treatments. Cellulosic residues from sawdust sequential 28 extraction showed great biosorption capacity (96%). In the presence of a metal mixture, oxidized sawdust had better selectivity for Cr^{3+} ions than for Ni²⁺. *Pinus caribaea* 29 30 biomass could be an environmental, inexpensive and renewable material for the 31 depollution of water laden with metallic trace elements. 32

Keywords (5): nickel, *Pinus caribaea* Morelet, modified sawdust, biomass recycle, water
 treatment.



52 **1. Introduction:**

Pollution by trace metals and their bioaccumulation in ecosystems is a global problem.
Metals are particularly present in rivers and groundwater because of natural processes
(rocks alteration and soil erosion) and anthropogenic activities which lead to
uncontrolled discharges of urban, industrial and agricultural wastewater (Lakherwal et
al., 2014).

58 New Caledonia is a South Pacific island characterized both by soils naturally rich in metallic trace elements and by nickel mining and industrial activities of worldwide 59 importance (Losfeld et al. 2015). One third of the main island is covered by ultramafic 60 rocks rich in transition elements as iron, nickel, cobalt, manganese or chromium which 61 can be released in surface waters (Gunkel-Grillon et al. 2014). In this archipelago, nickel 62 and chromium are two elements found in the urine of populations exposed to 63 concentrations above international reference values, in particular in children (St-Jean et 64 65 al. 2018).

To reduce the potential health risks associated to metals chronic exposure through the consumption of drinking water and for the removal of trace metal elements in aqueous solution, several treatment methods have been described (Lakherwal et al., 2014; Volesky et al., 2001; Lin and Juang 2002). Among them, biosorption have the advantages of being low cost, ecological, flexible, simple to implement and the possibility to be reuse (Volesky et al., 2003; Torres et al., 2020; Gupta et al., 2015; Demirbas et al., 2008; Veglio et al., 1997; Bailey et al., 1998).

73 Forestry by-products such as sawdust and bark have many advantages because they are 74 abundant, generally not toxic, and the macromolecules that compose them are known to bind metal ions (Gupta et al., 2015, Basso et al., 2002, Shukla et al., 2002). In particular, 75 the biomass obtained from trees of the genus Pinus has been described as good 76 77 biosorbent for removing metallic trace elements (Gundogdu et al., 2009; Argun et al. 78 2005, Ucun et al., 2003). For example, the Pinus halepensis untreated sawdust traps cadmium, copper and lead in aqueous solutions (Semerjian et al., 2010 and 2018). For 79 80 the removal of nickel (II) from aqueous environment, a review describes various agricultural solid wastes used as biosorbent like peanut hulls, pine bark or pine cone 81 (Raval et al., 2016). Another example is the used of treated mahogany sawdust as 82 83 biosorbent for the removal of nickel from aqueous solution (Chanda et al., 2021).

In the context of the bioressource use and circular economy perspective, our work is 84 focused on Pinus caribaea Morelet, a native conifer from Central America and 85 Caribbean islands. This species was widely planted for timber production in tropical 86 regions including New Caledonia, where it is nowadays the most exploited wood. This 87 work investigates the use of sawdust from P. caribaea as a biosorbent material for Ni^{2+} 88 removal and other metallic trace elements Co^{2+} , Cr^{3+} , Mn^{2+} ions from aqueous solutions. 89 This study allows the determination of optimal conditions (pH, contact time, initial Ni²⁺ 90 and biomass concentration) based on batch experiments. Isotherms of Langmuir and 91 Freundlich have been compared and kinetic parameters have been calculated by pseudo-92 second-order models. Extraction of parietal components of sawdust was carried out to 93 evaluate the biosorption capacity of cellulosic material. In addition, the selectivity of 94 sawdust has been evaluated according to four metals in solution (Ni²⁺, Cr³⁺, Co²⁺ and 95

96 Mn^{2+}) taken separately or in mixture to take into account the behaviour of biosorbent in 97 more realistic conditions.

98 The impact of different chemical treatments of natural sawdust was furthermore 99 investigated in this work. Two treatments and three oxidations of sawdust were carried 100 out by acidic and oxidation methods. The aim was to improve the capacity of nickel Ni²⁺ 101 removal compared to the natural biomass. The modification using an environmentally 102 friendly technique was chosen to evaluate the selectivity of this material.

103

104 **2. Materials and methods**

105 **2.1. Preparation of biosorbent material**

106 *2.1.1. Raw material*

Pine tree sawdust used in this work was from *P. caribaea* Morelet. The material for the preparation of biosorbent was obtained from local garden center. Before use, pine sawdust was washed in deionized water to remove surface impurities and then dried in an oven (Memmert Universal Oven UF1060 marque) at 40 °C for 4 days. Then, sawdust was ground into fine particle in a blender (Knife Mill GM 300) and sieved in a second crusher (Polymix PX-MFC 90 D) to the particles size required (0.2 or 0.5 mm).

113 *2.1.2. Extraction of polymers*

The parietal polymers of wood were obtained through successive extractions. The first step allows to get extractables like circulating sugars, tannins, mineral elements by an 80% hydroethanolic solution mixed with 10 g of sawdust powder. The solution was stirred for 7 min through Soxhlet apparatus. The residue was obtained by filtration and washed with ethanol 80%. For pectins, lignins, hemicelluloses and cellulosic residue extractions, protocols have been used according to the literature (Astier et al. 2010).

120 2.1.3. Modification of biomass

Five biomass modifications have been carried out by washing the sawdust (5 g, 0.2 mm) with different reagents following chemical protocols optimized from the literature (Hachem et al., 2012; Astier et al., 2010; Varmat et al., 1995).

124 The acidic sawdust (S_{H}^{+}) was obtained by washing the adsorbent material in a solution of 125 $H_2SO_4(0.1 \text{ M})$ under stirring for 2 h at 50 °C.

Fenton oxidized sawdust (S_F) was obtained by washing sawdust in 500 mL of water at 25 °C for 2 h. After filtration, a mixing solutions of hydrogen peroxide 50 mM and iron sulfate 0.5 mM was equilibrated in biomass at pH 3 by adding H_2SO_4 solutions (0.1 M). The solution was stirred at 25°C for 1 h. Finally, the biomass was filtered, washed and then stirred in a H_2SO_4 solution (0.1 M) for 1 h.

131 The oxidation technics to get dialdehyde (S_{CHO}), di-carboxylic ($S_{COOH(2)}$) and tri-132 carboxylic ($S_{COOH(3)}$) sawdust have been optimized from polysaccharide oxidation 133 described in the literature (Hachem et al., 2012; Varmat et al., 1995). Therefore, di-134 carboxylic sawdust ($S_{COOH(2)}$) was obtained by reaction of 1.5 g of dialdehyde sawdust

 (S_{CHO}) in 600 mL of sodium chlorite (0.3 M). Tri-carboxylic sawdust $(S_{COOH(3)})$ was 135 obtained from 3 g of S_{COOH(2)} in 300 mL of solution containing TEMPO (2.2,6,6-136 tetramethylpiperidin-1-yl)oxyl) (0.24 mmol), sodium bromide (3.63 mmol) and sodium 137 hypochlorite (7.26 mmol). Aldehyde functions formed on the biomass after oxidation are 138 139 determined using the Cannizzaro reaction (Pommerening et al., 1992). Indeed, 100 mg of modified sawdust was suspended in 20 mL of sodium hydroxide (0.1 M) and the 140 solution was stirred at 70°C for 15 min. The excess of sodium hydroxide was neutralized 141 by 0.05 M hydrochloric acid. 142

143 **2.2.** Characterizations of natural and modified adsorbent material

The functional groups on the surface of natural and modified biomass were identified by Fourier Transform Infrared (FTIR) spectrometer, ATR Frontier by PerkinElmer (spectrum range of 400 to 4000 cm⁻¹). The morphology and surface of natural and modified sawdust particles were observed by a scanning electron microscope (SEM, JSM-IT300 LV/LA).

149 The PH_{PZC} (Point of zero charge) of natural sawdust was determined by adding amounts of biosorbent at different pH values (Tran et al., 2017). In series of centrifuge tubes (50 150 mL), the pH was adjusted with 0.1 M HCl and 0.1 M NaOH as needed, to obtain the 151 appropriate pH range of 2, 3, 4, 5, 6, 7, 8, 9, 10 and 11. These pH values are denoted as 152 the initial pHs (pHi). 100 g of sample were added and solutions were completed with 153 deionized water. The solutions ns were shaken on a mechanical platform shaker at 250 154 rpm for 24 h and the final pH in each tube were measured and denoted as pH final (pH_f). 155 The PH_{PZC} was obtained from the plot of ΔpH (= pH_f – pH_i) versus pH_i or the plot of 156 PH_f versus PH_i. Experiments were carried out in triplicate and the mean value was 157 158 recorded.

159 **2.3. Preparation of metal ions solutions and analytical methods**

160 A solution containing 5 g/L Ni²⁺ ions was prepared from a solution of Ni(NO₃)_{2.6H₂O 161 (Sigma-Aldrich) in a volumetric flask with deionized water. The working solution was 162 carried out by appropriate dilutions with varying concentration (mg/L) of the mother 163 solution at a given pH. Other metals solutions were prepared in the same way from 164 solutions of Co(NO₃)_{2.6H₂O, Cr(NO₃)_{3.9H₂O and Mn(NO₃)_{2.4H₂O respectively.}}}}

An Inductively Coupled Plasma Optical Emission Spectrometry (ICP-OES 730ES Varian) was used to analyze metal ions concentrations in experimental aqueous solutions. A reference scale of Ni²⁺ solutions at known concentrations was realized in the range among 0.005 to 20 mg/L as a calculus base for the ICP-OES to determine further concentrations. Samples with an initial Ni²⁺ concentration higher than 20 mg/L were prepared by adequate dilution to avoid any error during the analyzing process.

171 **2.4. Biosorption**

The biosorption of Ni^{2+} on the pine sawdust was studied through batch technique by studying the effect of particle size, pH, contact time and initial adsorbate concentration. The general method was as follows: 10 mL of nickel solutions at varying concentrations (0.5 to 1000 mg/L) was in reaction with biomass (1 to 20 mg) at pH 5 for the first batch. Values of pH of solutions were adjusted to desire levels (pH = 1 to 9) using diluted NaOH or HCl solutions. 178 The suspension in the tube was stirred at 25 °C on a mechanical platform shaker at 250 179 rpm for 16 h to reach equilibrium. The influence of contact time on adsorption efficiency 180 and isotherm analysis were investigated by shaking the tubes at different times (10 s to 181 360 min). Biomass was removed by vacuum filtration through 0.45 μ m nitrocellulosic 182 membrane, and the concentration of Ni²⁺ ions in the filtrate was analyzed using ICP-183 OES. All the biosorption experiments were repeated in triplicate.

184 Compared to the initial metal concentration, the adsorption efficiency in the following 185 **Eq.** (1) was calculated as a percentage of adsorbed metal in equilibrium. Adsorption 186 capacity is the amount of metal adsorbed per mass unit of sawdust according to **Eq.** (2).

187 (1) Metal removal efficiency (%) = $\frac{(Ci-C)}{Ci} \times 100$ 188

189 (2)
$$q (mg/g) = \frac{(Ci-C).V}{m}$$

190

191 Where, Ci and C are the initial and equilibrium concentrations of metals ions (mg/L) in 192 the solution, q is the adsorption capacity (mg/g) or the mass of metal ion solution 193 adsorbed per unit mass of sawdust (mg/g), V is the volume of solutions (L) and m is the 194 sawdust mass (g).

195 **2.5. Desorption**

196 The Ni²⁺ ions retained by pine sawdust have been extracted by experiments in a batch 197 system by investigating different concentrations of two acids: hydrochloric acid (0.01, 198 0.1 and 0.5 M) and sulfuric acid (0.005, 0.05 and 0.25 M). Previously dried, the biomass 199 loaded with Ni²⁺ ions was stirred for 16 h in 10 mL of HCl or H₂SO₄ solutions. The 200 solution was filtered through 0,45 μ m nitrocellulose membrane and analyzed by ICP 201 spectrometer to determine the amount of Ni²⁺ desorbed.

202 **2.6. Adsorption isotherm models**

The relationship between the amount of Ni^{2+} ions adsorbed and its equilibrium concentration in aqueous solution was established by models of Langmuir and Freundlich which are the most commonly used (Langmuir et al., 1918; Freundlich et al., 1907). Experiments were conducted at different concentration of biomass (1 to 20 g/L) with different Ni²⁺ initial concentration (0.5 to 200 mg/L).

208 **2.7. Adsorption kinetics**

Most adsorption systems were reported to follow a pseudo second-order kinetic models (Ho et al., 1999). Experiments were carried out at various periods ranging from 10 seconds to 360 minutes at two pH values to study the effect of acidic and basic conditions.

213 **2.8.** Biosorption of a mixture of metals (Co²⁺, Cr³⁺, Mn²⁺, Ni²⁺)

The biosorption capacities of natural and Fenton oxidized sawdust were assessed for the removal of metal ions Co^{2+} , Cr^{3+} , Mn^{2+} and Ni^{2+} ions from aqueous solutions. Metal solutions were evaluated separately and in a mixture under optimum parameters 217 previously determined (initial metal ion concentration = 5 mg/L (alone or in a mixture), 218 5 g/L of pine biomass, pH=8).

219 **2.9. Biomass recycling**

To evaluate the reusability of natural pine sawdust, biosorption-desorption cycles were repeated five times using the same concentrations (5g/L of sawdust). 5 mg/L of initial Ni²⁺ concentration solution was used for biosorption and desorption was performed with 10 mL of 0.1 M HCl solution for 16 h.

3. Results and discussion

225


226 **3.1.** Physicochemical characterization of natural and modified sawdust

227 228

229

3.1.1. Fourier Transform Infrared (FTIR) Spectroscopy

The infrared spectra of the natural and modified pine sawdust were carried out to 230 determine the type of functional groups present in the sawdust surface (Fig. 1). All 231 spectra shared characteristic absorption bands around 1600-1700 cm⁻¹, 2900 cm⁻¹ and 232 3300 cm⁻¹ which has been assigned respectively to the stretching vibrations of carbonyl 233 group (C=O), C-H and OH stretching. Nevertheless, we can observe some modifications 234 after the different chemical treatments. Thus, aldehydes groups (S_{CHO}) in pine sawdust is 235 associated to bands around 2855-2849 cm⁻¹ (vibrational stretching of C-H bands) and 236 1700 cm⁻¹ (C=O) higher than natural sawdust (Stuart et al., 2005). Bands attributed to 237 COOH groups present at 1500-1600 cm⁻¹ (C=O), and 1200 cm⁻¹ (C-O) are higher in 238 dicarboxylic and tricarboxylic spectra. Generally, band intensities increase in the same 239 direction as the sawdust oxidation degree. The oxidation of aldehyde functions in 240 241 carboxylic acid function is reflected in a decrease of band intensity around 1740 cm⁻¹ versus a wide band around 1600 cm⁻¹ for dicarboxylic and tricarboxylic sawdust spectra. 242 The presence of band for dicarboxylic sawdust is translated by a non-complete reaction 243 because all aldehydes haven't been oxidized. The spectra of acidified sawdust allow to 244 observe a little increase in the intensity of the band around 1700 cm⁻¹ (C=O aldehyde) as 245 a sign of the disappearance of hemiacetal functions in acid treatment. For Fenton 246 oxidized sawdust, the band characteristic of aromatic rings (1600 cm⁻¹ stretching of 247 C=C) was decreased following degradation. 248



250 251


252

Fig. 1. FTIR spectra of natural, treated and oxidized sawdust

254 3.1.2. Scanning Electron Microscopy (SEM) Analysis and Energy Dispersive X 255 Ray (EDX) Spectroscopy.

256

The microscopic analysis SEM confirms the difference in structure between natural and 257 modified sawdust (Fig. 2). Natural sawdust had fibrous and rough surface with 258 heterogeneous structure similar to a spongy aspect. The obtained S_{H+} presented many 259 pits and fissures, possibly because of the powerful dehydrating of sulfuric acid. Oxidized 260 sawdust S_F, S_{CHO} and S_{COOH} had irregular, heterogeneous surface characterized by 261 cracks, the pore volume increase. Thus, oxidized reagents disturb the surface of sawdust 262 making them more available to metals. The adsorption mechanism occurring in pores 263 considers interactions such as electrostatic attraction, hydrogen bonding, surface 264 265 precipitation, cation exchange. These interactions depend on the characteristics of the porous adsorbents and adsorbate (Tran et al., 2017). 266





268 269

Fig. 2. Characterizations by SEM of natural sawdust (a) at 1600x, treated SH+ (b), SF (c) at 650x and oxidized sawdust SCHO (d), SCOOH (e) at 650x.

The EDX spectroscopy gives an overview of the sawdust elemental composition before 270 271 and after nickel biosorption (Table 1s, Fig 1s and 2s in supplementary data). The natural 272 sawdust contains atoms on its surface like carbon and oxygen present in the structural 273 polymers of wood. Other elements are present such as minerals: calcium, manganese, silicon, iron or copper. These elements were naturally absorbed by the biosorbent in its 274 275 environment. For example, manganese and calcium are found in P. caribaea needle samples in works of Carrions N. et al., 1987. Chlorine and nickel appear in addition on 276 the sawdust after biosorption, chlorine comes from the HCl acid added during pH 277 adjustment. This experiment shows that nickel is present on the surface of pine sawdust 278 after biosorption of 5 mg/L of nickel solution. This element is not the only one present 279 on the surface of the sawdust, which raises the question of the occupation of active sites 280 (Supplementary Data). 281

282

3.1.3. Point of zero charge determination

283 284

The point of zero charge (pH_{PZC}) of natural sawdust in aqueous solution was obtained by plotting pH final against pH initial or (pH initial - pH final) against pH initial according to **Fig.3**. For this biomass, the pH_{PZC} was around 4.6. At a pH less than pH_{PZC}, the biosorbent is protonated and the surface positively charged, is able to capture anions. When pH is higher than pH_{PZC}, the biosorbent surface is negatively charged and becomes a trap for the cations. The nickel (Ni^{2+}) is more easily trapped in basic environment. The mechanism involved is electrostatic interaction (Tran et al., 2017).




Fig. 3. Point of zero charge of natural sawdust, pH final against pH initial (a) and Δ pH against
 pH initial (b).

293

292

3.2. Modification yield and quantitative dosage

- 298
- *3.2.1. Modification yield*
- The mass yields obtained were 92.4, 93.8, 95.0 and 92.0% respectively for S_{H+} , S_{F} , S_{CHO} , and S_{COOH} . A low loss of mass was observed, the sawdust is reactive to oxidation even after several steps.

303	3.2.2. Quantitative determination of aldehyde functions (S_{CHO})
304	
305	The oxidation reaction of polysaccharides by sodium hydroxide was confirmed through
306	the determination of the aldehyde functions present on the sawdust. The Cannizzaro

reaction involves the action of base on the aldehyde functions leading to the establishment of a stoichiometric ratio between the concentration of hydroxyl ions consumed and the initial concentration of the dialdehyde groups. The aldehyde functions rate was 12.7 mmol per gram of oxidized pine sawdust. Compared to the estimated value (4.08 mmol) this value is higher, which suggesting that the oxidation was reacted on other polysaccharides.

3.3. Factors affecting efficiency of Ni²⁺ biosorption on sawdust


315 316 317

313

314

*3.3.1. Initial concentration of Ni*²⁺ and size of particles

High metal removal was attained (80%) at Ni²⁺ ions concentration of 0.5 mg/L (Fig.4).
The biosorption of metal ions has stabilized for higher concentration of Ni²⁺ because of
saturation of binding sites on the adsorbent. In this case, the additional number of metal
ions in solution was competing for a limited number of adsorption sites (Ucun et al.,
2003).



324 325




Fig. 4. Effects of initial concentration of Ni^{2+} and size of particles.

327

328 *3.3.2 Adsorbent concentration*

Experiments was carried out with sawdust concentrations ranging from 0 to 20 g/L and 329 different Ni²⁺ concentrations (10-100 mg/L) at pH 8 for 16 h. The percent removal of 330 metal ions was increased in the same direction than the mass of sawdust until a 331 quantitative retention for the adsorbent mass of 5 g/L in Fig. 5. It is apparent that the 332 Ni²⁺ adsorption evolves with the weight of sawdust because of an increase of availability 333 334 of exchangeable sites. At a moment, the maximum adsorption efficiency of a metal was achieved even after additional added of binding sites from sawdust. Thus, the adsorption 335 efficiency decreases with the increases of the quantity of biomass. 336



339

Fig. 5. Effect of adsorbent mass.

340

341

342

As an important parameter in the sorption process, pH can act on the functional groups and the charges affecting interactions between ions in solution (Akmal et al., 2012).

3.3.3. pH of suspension

Under highly acidic conditions (pH 1-3), the amount of Ni²⁺ uptake was minimal (<0.2 mg/g) while the sorption was enhanced in the pH ranging of 3 to 9, showing a maximum adsorption at pH 9 (**Fig. 6**). At lower pH values, high concentration of hydronium ions are in competition with Ni²⁺ ions for the active sites on the sawdust surface positively loaded. When pH increase, the competing effect of hydronium ions decreased, Ni²⁺ ions have electrostatic attraction with the surface of sawdust, negatively loaded, allowing a favorable process for the metal ions adsorption (Shukla et al., 2002 and 2005).

Nickel have four different species Ni^{2+} , $Ni(OH)^+$, $Ni(OH)_2$ and $Ni(OH)_3$ but the predominant species is Ni^{2+} at pH 9 (Gonsalvesh et al., 2016). When the pH increased above pH 9, the percentage of nickel removal decreased by the fact that soluble hydroxyl complexes are formed at higher pH.

The increase observed around pH 4 seems to confirm the acidic character of the unmodified pine sawdust surface that corresponds to pKa of aromatic carboxylic acids. Indeed, Salazar J.J et al. described a high concentration of acid groups, mainly phenolic groups present in the surface of the main components of pine sawdust (Salazar-Rabago et al., 2017).

361






Fig. 6. Effect of pH for the adsorption of 50 mg/L of Ni²⁺ in sawdust (5g/L).

366

367 3.3.4 Contact time

368

Under basic condition **Fig. 7(a)**, a maximum adsorption rate (90%) was achieved instantly and then slowly decreased until equilibrium was reached (2 h, 70% of biosorption). The formation of soluble hydroxyl complexes can lead to decrease of adsorption (Shukla et al., 2005).

Under acidic condition (pH 4), the adsorption rate was increased during the first five minutes and reach equilibrium after 1h according to Fig. 7(b). An adsorption efficiency of 57% was recorded for 50 mg/L. The equilibrium in acidic conditions was reached more rapidly but at lower percentage of adsorption as compared to the basic condition.




Fig. 7. Effect of contact time under basic (a, pH 8) or acidic (b, pH 4) conditions in 5g/L of
 adsorbent.

386 **3.4. Adsorption isotherms**

387 *3.4.1 Langmuir isotherm:*

388

Langmuir isotherm is valid for monolayer adsorption capacity onto a surface containing a finite number of equivalent adsorption sites. This model respects the following assumptions: the number of active sites on the surface of the adsorbent is fixed and has the same energy, desorption is possible, no other adsorption can occur on the occupied site and no interaction between the adsorbed species. The following nonlinear and linear forms (Eq. 3 and Eq. 4) model this isotherm (Langmuir et al., 1918).

$$(3) \quad \frac{qe}{qmax} = \frac{b.Ce}{(1+b.Ce)}$$

397 (4)
$$\frac{Ce}{qe} = \frac{1}{b} \cdot q_{max} + \frac{1}{q_{max}} C_e$$

Where q_e and q_{max} (mg/g) are the amount of metal ions adsorbed per unit mass of the 398 399 adsorbent at equilibrium and at maximum respectively, b (L/mg) is the adsorption equilibrium constant related to the affinity of the binding sites and Ce (mg/L) is the 400 adsorbate concentration at equilibrium. 401

402 The separation factor R_L is employed for isotherms that obey the Langmuir model at different initial adsorbate concentrations. This equation is presented below (Eq. 5). 403

404 (5)
$$R_L = \frac{1}{1+b.CO}$$

405

Where C_0 (mg/L) is the initial concentration of the adsorbate. The separator factor is 406 407 commonly used to evaluate the adsorbent capacity. If $0 > R_L > 1$, the adsorption is favorable while if $R_L=0$, RL=1 and higher than one, the adsorption is unfavorable (Fu et 408 409 al., 2007).

410 Table 1 presents the values of Langmuir parameters for nonlinear and linear modeling and separator factor R_L. The non-linear parameters were calculated according to the 411 method described by Tran et al., 2017. The q_{max} values (number of active sites on the 412 biosorbent) are higher when the concentration of sawdust is low and the R_L values are 413 between 0 and 1 so the adsorption is favorable. 414

415

416 Table 1. Parameters of Langmuir isotherm models for Ni²⁺ adsorption on *P. caribaea* sawdust, comparison of linear and nonlinear models. 417


Sawdust	Langmuir linear			Langmuir nonlinear		Comparison		R _L
(g/L)	parameters			parameters				
	q _{max}	b	\mathbb{R}^2	q _{max}	b (L/mg)	Δq_{max}	Δb	
	(mg/g)	(L/mg)		(mg/g)				
1	5.692	0.067	0.869	7.274	0.018	1.582	0.049	0.937-0.982
10	1.890	0.097	0.994	1.952	0.067	0.062	0.03	0.597-0.912
15	1.705	0.071	0.994	1.696	0.073	0.009	0.002	0.478-0.484
20	1.439	0.073	0.988	1.367	0.086	0.072	0.013	0.366-0.407

418

419 The linearization used for Langmuir is the form $(C_e/q_e = f(C_e))$ which shows a reliable 420 similarity with the nonlinear fit. The parameter values appear to be close for the linear and non-linear fit and the largest differences in values are found for low biosorbent 421 concentrations (1g/L). Recent work has provided a critical analysis of the linear model. 422

Indeed, the dispersion of the points is arranged according to a Gaussian distribution and 423

the error distribution is uniform at all points. However, according to a non-linear model, this rarely happens with adsorption isotherms. In our linearization, C_e is in both x and y and the correlation is overestimated. The linearization leads to a good fit but is not only significant of Langmuir hypotheses. Thus, high R² values do not prove that the Langmuir mechanism occurs exclusively and is no sufficient to compare the experimental values and isotherm parameters (González-López et al., 2021, Tran et al., 2017). Hence, the nonlinear model allows a reliability of the parameters (**Fig. 8**).



431



Fig. 8. Curves fitting of non-linear Langmuir equation.

433

- 434 *3.4.2 Freundlich isotherm*
- 435

The Freundlich isotherm implicates a removal of metal ions on a heterogeneous
adsorbent surface. The model is suitable for multilayer adsorptions and describes a
reversible adsorption process (Freundlich et al., 1907). The equation of Freundlich is
expressed in nonlinear and linear forms in Eq. (6) and Eq. (7) respectively.

440 (6)
$$q_e = K_f. C_{e.}^{1/n} f$$

441 (7) Log
$$q_e = \log K_f + \frac{1}{n_f} .\log C_e$$

442 Where, $K_f ((mg/g)/ (mg/L)^n)$ is the constant related to adsorption capacity, n_f is the 443 Freundlich equilibrium constant, a parameter related to adsorption intensity.

444 Linearization of Freundlich model by logarithmic form allows the determination of 445 constants K_f and n_f by the plot of log q_e versus log C_e . 446 The **Table 2** summarize Freundlich isotherms constants for Ni^{2+} adsorption in pine 447 sawdust and allows the comparison of nonlinear and linear models. The K_f relative to the 448 adsorption capacity increases when the biosorbent concentration is low. These results 449 showed the decrease of efficiency of Ni²⁺ removal despite the addition of adsorbent and 450 the increased of Ni²⁺ concentration in solution.

451	Table 2. Parameters of Freundlich isotherm models for Ni2+ adsorption on P. caribaea sawdust,
452	comparison of linear and nonlinear models.

Sawdust	Freundlich linear parameters			Freundlich nonlinear		Comparison	
(g/L)				parame	eters		
	$K_f(mg/g)$	$n_{\rm f}$	\mathbb{R}^2	$K_f(mg/g)$	n _f	ΔK_{f}	$\Delta n_{\rm f}$
1	0.545	2.487	0.912	0.325	2.380	0.22	0.107
10	0.128	3.399	0.850	0.047	2.444	0.081	0.955
15	0.04	1.514	0.928	0.035	2.234	0.005	0.72
20	0.003	1.538	0.957	0.020	2.58	0.017	1.042

453

The n_f values higher than 1 highlights a physical process. The values for the exponent n in the range of 0-10 suggest favourable adsorption (Kumar et al., 2006a). The K_f values is lower in the non-linear fit than linear fit. The comparison of the parameters shows that the values are close and the greatest difference is found for the concentrations of 1 and 20 g/L.

459 **3.5. Adsorption kinetic study**

Kinetic models aim to understand the interactions between the adsorbent and the adsorbate, and to provide information on the complex mechanism of adsorption. The pseudo-second order models (PSO) is the most commonly used equation and suppose that the rate-limiting step involves chemisorption (González-López et al., 2021). The two equation (nonlinear and linear) Eq.8 and Eq. 9 respectively are presented below.

465 (8):
$$q_t = \frac{qe^2 \cdot k^2 \cdot t}{1 + q_e \cdot k^2 \cdot t}$$

466 (9):
$$\frac{t}{q_t} = \frac{1}{qe^2 \cdot k^2} + (\frac{1}{qe} \cdot t)$$

467 Where k (l/min) is the second-order rate constant, t (min) the time, q_t and q_e (mg/g) are 468 the amounts of adsorbate uptake per mass of adsorbent at any time t (min) and at 469 equilibrium respectively.

The linear form describes the kinetic of Ni²⁺ biosorption with a high correlation coefficient ($R^2 > 0.999$) for initial metal concentration of 5.0 mg/L according to **Fig. 9**. The linearized models help for predicting the initial k and q_e for non-linear models. 473 Hence, the second-order rate constant (k) was 43.96 and the theorical amount of 474 adsorbed metal ions at equilibrium was measured at 0.517 mg/g (q_e , calculated), whereas 475 the experimental value was 0.798 mg/g (q_e , experimental).







Fig. 9. Pseudo-second-order plot of Ni²⁺ adsorption on *P. caribaea* sawdust.

478

This linearized equation give a good fit but t is in the two axis so the correlation is
overestimating and could positively change the conditions (González-López et al.,
2021). Because of the error distribution, non-linear regression is preferred (Fig. 10).










485 3.6. Study of desorption of Ni²⁺ ions 486

487

After desorption, the biosorbent should recover its original form as well as its adsorption 488 capacities. Desorption process requires effective, cheap and non-destructive reagents for 489 the biomass. Dilute solutions of hydrochloric acid HCl and sulfuric acid H₂SO₄ were 490 selected as eluents to desorb Ni²⁺ ions from the metal-loaded pine biomass. Under acidic 491 conditions, protons displace metal cations such as Ni²⁺ from the binding sites of the pine 492 493 sawdust.





495

Fig. 11. Ni²⁺ desorption efficiency of sawdust with HCl or H₂SO₄ treatments.

The percentage of Ni²⁺ ions removal from pine sawdust surface with HCl was constant 496 (Fig. 11), but the highest desorption were observed for 0.01 and 0.1 M of HCl (82.0 and 497 81.0 % respectively). For 0.5 M of HCl, the Ni²⁺ desorption was bitten decreased. For 498 the three concentrations of H₂SO₄, the best rate of desorption is observed for a 499 concentration of 0.01 M showing that higher concentrations of sulfuric acid were less 500 efficient in releasing Ni²⁺ ions. Sulfuric acid globally presented lower desorption 501 capacities than hydrochloric acid. However, a complete desorption of Ni²⁺ ions by using 502 HCl or H₂SO₄ could not be obtained, which might be due to metal ions being trapped in 503 the intrapore of the sorbent's surface and therefore, difficult to be released (Serencam et 504 505 al., 2008). Finally, 0.1M of HCl was selected for the other experiments of this study.

506

3.7. Evaluation of removal capacity of modified sawdust


507


Cellulose is the main component of sawdust (73.1%) and better adsorbs Ni²⁺ ions in 508 solution (96.0%) than natural pine sawdust (Fig. 12). This result is confirmed by the 509 literature, which confirms the high removal capacity of cellulosic polysaccharides and in 510 particular, hydroxyl groups on their surface (Gupta et al., 2015; Basso et al., 2002). 511

512 Studies of Basso and al. have proved that the presence of cellulose and hemicelluloses in

513 plant biomass improved the biosorption potential (Basso et al., 2002).

514





518

515

As a heterogenous material, sawdust contains numerous cations like calcium and sodium 519 520 naturally fixed on the ion exchange sites, which reduce the retention capacities of metal 521 in solution (Hawari et al., 2005). To overcome this drawback, this material was stabilized through chemical activation, for example by treatment with acid or oxidative 522 degradation. These chemical modifications aim to adding functional groups on the 523 524 polysaccharide structure or treatments that modifying the physicochemical surface properties. Adsorption results depend on the chemical modification as well as the metal 525 considered. Compared with natural sawdust according to Fig. 13, all modifications were 526 more effective for the Ni²⁺ uptake. Acid treatment seems to be less effective than 527 oxidized reactions. Mentioned above, the surface S_H⁺ sawdust seems to be damaged 528 compared to smooth surface of oxidized pine sawdust. All of these modifications are 529 characteristics of increasing surface area making the sites more accessible. The 530 531 adsorption maximum of 98.3% was observed for tricarboxylic sawdust. This result confirms the proportionality between the number of carboxylic acid functions formed 532 and the amount of ions bounds (Vinícius et al., 2007). The chemical nature and spatial 533 arrangement of binding sites can influence the binding of cations to organic matter. 534 Indeed, carboxylic sites attached to adjacent carbon atoms and spaced on a ring, are 535 more selective to multivalent cations (Talibudeen et al. 1981). 536 537


3.8. Biosorption of Co^{2+} , Cr^{3+} and Mn^{2+} ions by natural and Fenton oxidized


539 sawdust

As a chemical process for wastewater treatment, oxidation by Fenton's reagents is based 541 on the catalytic decomposition of H_2O_2 in presence of iron salts (Fe²⁺). As a cost-542 effective source of hydroxyl radical (OH), this method has many advantages as 543 simplicity of design, safe operation, high efficiency, availability and short reaction time 544 (Nevens et al., 2003). The Fig. 13 shows that metal adsorption was different as function 545 of active sites and functional groups on the surface of the biosorbent. This behavior is 546 attributed to selectivity of biosorption, which depend on characteristic of metal ions such 547 as electronic charge of the valence layer, the counter ions in solutions, hydration 548 enthalpy, ionic radius, coordination number, electron configuration or electronegativity 549 (Gorgievski et al., 2013; Zeraatkar et al., 2016). 550

551

540






For single metal uptake (**Fig. 13,b**), natural pine sawdust showed a greater affinity than for Cr^{3+} (84.1%) followed by Ni²⁺(72.6%) whereas Fenton oxidized pine sawdust had better adsorption capacity for Ni²⁺(98.0%) followed by Co²⁺(65.8%). Oxidation under 559 Fenton conditions was the most favorable treatment for the adsorption of nickel in solution. As the metals are usually found in mixture in nature, experiments with a 560 mixture of four metals were conducted (Fig. 13, a). Sawdust is a complex material with 561 many possible binding sites. In a mixture, metal is competed with another inducing 562 selectivity according to the available sites on sawdust surface. Results show that in the 563 presence of a mixture of these four metals, natural sawdust and Fenton oxidized sawdust 564 had great affinity for Co^{2+} and Cr^{3+} . Affinity of metal ion for biosorbent takes into 565 consideration all properties of metal ion. 566

567 **3.9. Biomass reusability cycles**

568

After the first cycle, the biosorption of natural pine sawdust capacity increased then barely changed before decreasing after the fifth cycle according to **Fig. 14**.



571

Fig. 14. Reuse of natural pine sawdust for Ni2+ biosorption-desorption cycles (initial Ni2+
concentration = 5.0 mg/L, sawdust concentration = 5.0 g/L, pH = 8, desorption solution: 10 mL
of 0.1 HCl at 16 h).

On the contrary, the desorption efficiency slowly increased until quantitative desorption 575 after the fourth cycle. These results disagree with results obtained in other studies in 576 which HCl decreases metal adsorption capacity of the biosorbent in successive cycles by 577 damaging metal binding sites (Mehta et al., 2005). Desorption using HCl solution can 578 579 cause a change in sawdust structure as seen in acidic treatment modification, thus gradually increasing the capacity of biosorption in the first cycles. This structural 580 modification in acidic conditions can also explain the increase of Ni²⁺ desorbed which 581 could come from initial ions accumulated into intrapore of the biosorbent during 582 previous cycles. 583

584 **Conclusion**

P. caribaea sawdust is an ecological, available, inexpensive and effective biosorbent to 585 reduce in aqueous solutions metallic trace elements (Ni²⁺, Co²⁺, Cr³⁺, Mn²⁺) which are 586 present in rivers and groundwater of New Caledonia. Our work defined the optimal 587 parameters (pH, particle size, biomass and initial concentration) for Ni²⁺ and adsorption 588 589 rate was reaching equilibrium in short time. From a sustainable development perspective, we proven than Pinus caribaea sawdust can be reuse in five cycles after 590 regeneration with a good efficiency. Biomass modifications by acid treatment and 591 oxidative reactions can be accomplished in good yields and improve the metal binding 592 capacities on sawdust. Selectivity of metals on natural sawdust versus Fenton oxidized 593 sawdust is highlighted for Ni^{2+} and Cr^{3+} while variation are observed when metals are in 594 mixture. P. caribaea sawdust could thus become an attractive material for the 595 development of water purification techniques by biosorption for depollution installations 596 adapted to the context of tropical islands producing this *Pinus* species in forestry. Many 597 studies focus on the use of biomass to remove heavy metals from water but rarely lead to 598 599 concrete applications because the treatment of biomass to remove metals require acidic environment and thus generates new waste. Metallurgical extraction techniques have 600 evolved over the last decades with the emergence of hydrometallurgy. This technic 601 602 currently applied in New Caledonia involve the use of acidic aqueous solutions for the recovery of metals from ores. Our results thus fit in an island context for which a 603 technical solution could be associated with industrial metallurgic complexes to recycle 604 605 the biomasses used to decontaminate water.

606

607 CRediT authorship contribution statement

Conceptualization: CS, NL, VS. Methodology: CS, NL. Validation: CS, TG, ML, NL,
VS, FB, VC. Formal analysis: CS, TG, VC. Investigation: CS, TG, ML, MM, NL.
Resources: MM, NL. Writing - Original Draft: CS. Writing - Review & Editing: MM,
FB, NL, VS. Visualization: CS. Supervision: NL. Project administration: NL. Funding
acquisition: NL

613

614 Acknowledgements

The authors are thankful to the research and development institute (IRD) of New
Caledonia particularly the LAMA for analysis of metal trace elements. Thank you for
the microscopy platform of University of New Caledonia and analysis equipment of
PEIRENE Laboratory of University of Limoges.

619

620 Declaration of Competing Interest

621 The authors declare no conflict of interest.

623 **References**

Akmal, S.K., Malathi, J.J., Vijaya, Y., Popuri, S.R., Subbaiah, M.V., 2012. Biosorption of Ni(II)
from aqueous solutions by Syzygium cumini bark powder: Equilibrium and kinetic studies.
Desalination Water Treat. 47, 59-68. <u>https://doi.org/10.1080/19443994.2012.696430</u>

Argun, M.E., Dursun, S., Gur, K., Ozdemir, C., Karatas, M., Dogan, S., 2005. Nickel adsorption
on the modified pine tree materials. Environ. Technol. 26, 479–488.
https://doi.org/10.1080/09593332608618532

630 3. Astier, C., 2010. Adsorption des éléments traces métalliques par les écorces forestières, un
631 co-produit de la filière bois. Optimisation des propriétés par modifications induites par voies
632 chimique et biologique. PhD Thesis. p. 161-163/141.

4. Bailey, S.E., Olin, T.J., Mark Bricka, R., Dean Adrian, D., 1998. A review of potentially low-cost
sorbents for heavy metals. Wat. Res. 33 (11), 2469-2479. <u>https://doi.org/10.1016/S0043-</u>
<u>1354(98)00475-8</u>

5. Basso, M.C., Cerrella, E.G., Cukierman, A.L., 2002. Lignocellulosic materials as potential
biosorbents of trace toxic metals from wastewater. Ind. Eng. Chem. Res. 41, 3580–3585.
https://doi.org/10.1021/ie020023h

639 6. Carrions, N., Benzo, Z., Eljuri, E., Ippoliti, F., Flores, D. 1987. Determination of manganese,
640 calcium, magnesium and potassium in pine (pinus caribaea) needle samples by flame atomic
641 absorption spectrometry with slurry sample introduction. Journal of analytical atomic
642 spectrometry, Issue 8.

7. Chanda, R., Hamza Mithun, A., Abu Hasan, Md., Kumar Biswas, B. 2021. Nickel removal from
aqueous solution using chemically treated mahogany sawdust as biosorbent. Hindawi. Journal
of Chemistry. Article ID 4558271, 10 pages https://doi.org/10.1155/2021/4558271

- 646 8. Demirbas, A., 2008. Heavy metal adsorption onto agro-based waste materials: A review. J.
 647 Hazard. Mater. 157, 220–229. https://doi.org/10.1016/j.jhazmat.2008.01.024
- 648 9. Freundlich, H., 1907. Über die Adsorption in Lösungen. Z. Phys. Chem. 57, 385-470.
 649 <u>https://doi.org/10.1515/zpch-1907-5723.</u>
- 650 10. Fu, L., Huang, X., Wang, J., 2007. Comment on removal of supranol yellow 4GL by
 651 adsorption onto Cr-intercalated montmorillonite. Journal of Hazardous Materials. 148, 771652 772.

653 11. Gonsalvesh, L., Marinov, S. P., Gryglewicz, G., Carleer, R., Yperman, J., 2016. Preparation,
654 characterization and application of polystyrene based activated carbons for Ni(II) removal from
655 aqueous solution. Fuel Processing Technology. 149, 75–85

656 12. González-López, M.E., Laureano-Anzaldo, C.M., Pérez-Fonseca, A.A., Arellano, M., Robledo657 Ortí, J.R. 2021. A Critical Overview of Adsorption Models Linearization: Methodological and

658 Statistical Inconsistencies, Separation & Purification Reviews, DOI: 659 10.1080/15422119.2021.1951757

Gorgievski, M., Božíc, D., Stankovíc, V., Strbac, N., Serbula, S., 2013. Kinetics, equilibrium
and mechanism of Cu2+, Ni2+ and Zn2+ ions biosorption using wheat straw. Ecol. Eng. 58, 113–
122. https://doi.org/10.1016/j.ecoleng.2013.06.025

Gundogdu, A., Ozdes, D., Duran, C., Bulut, V.N., Soylak, M., Senturk, H.B., 2009. Biosorption
of Pb(II) ions from aqueous solution by pine bark (Pinus brutia Ten.). Chem. Eng. J. 153, 62–69.
https://doi.org/10.1016/j.cej.2009.06.017

Gunkel-Grillon, P., Laporte-Magoni, C., Lemestre, M., Bazire, N., 2014. Toxic chromium
release from nickel mining sediments in surface waters, New Caledonia. Environ Chem Lett. 12,
511-516. https://doi.org/10.1007/s10311-014-0475-1

669 16. Gupta, V.K., Nayak, A., Agarwal, S., 2015. Bioadsorbents for remediation of heavy metals:
670 Current status and their future prospects. Environ. Eng. Res. 20, 1–18.
671 https://doi.org/10.4491/eer.2015.018

17. Hachem, K., Astier, C., Chaleix, V., Faugeron, C., Krausz, P., Kaid-Harche, M., Gloaguen, V.,
2012. Optimization of Lead and Cadmium Binding by Oxidation of Biosorbent Polysaccharidic
Moieties. Water Air Soil Pollut. 223 (7), 3877-3885. https://doi.org/10.1007/s11270-012-1156y

18. Hawari, A.H., Mulligan, C.N., 2005. Biosorption of lead(II), cadmium(II), copper(II) and
nickel(II) by anaerobic granular biomass. Bioresour Technol. 97 (4), 692-700.
https://doi.org/10.1016/j.biortech.2005.03.033

Ho, Y.S., Mckay, G., 1999. Pseudo-second order model for sorption processes. Process
Biochem. 34 (5), 451-456. https://doi.org/10.1016/S0032-9592(98)00112-5

681 20. Kumar, K. 2006. Comments on "adsorption of acid drye onto organobentonite". Journal of682 Hazardous Materials B 137, 638-639.

683 21. Lakherwal, D., 2014. Adsorption of Heavy Metals: A Review, J. Environ. Dev. 4 (1), 41-44.

Langmuir, I., 1918. The adsorption of gases on plane surfaces of glass, mica and platinum. J.
Am. Chem. Soc. 40, 1361–1403. https://doi.org/10.1021/ja02242a004

Lin, S.H., Juang, R.S., 2002. Heavy metal removal from water by sorption using surfactantmodified montmorillonite. J. Hazard. Mater. 92, 315–326. https://doi.org/10.1016/S03043894(02)00026-2

689 24. Losfeld, G., L'huillier, L., Fogliani, B., Jaffré, T., Grison, C., 2015. Mining in New Caledonia:

690 environmental stakes and restoration opportunities. Environ. Sci. Pollut. Control Ser. 22, 5592–
691 5607. https://doi.org/10.1007/s11356-014-3358-x.

692 25. Mehta, S.K., Gaur, J.P., 2005. Use of algae for removing heavy metal ions from wastewater:
693 progress and prospects. Crit. Rev. Biotechnol. 25, 113–152.
694 https://doi.org/10.1080/07388550500248571

26. Neyens, E., Baeyens, J., 2003. A review of classic Fenton's peroxidation as an advanced
oxidation technique, J. Hazard. Mater. 98, 33-50. <u>https://doi.org/10.1016/S0304-</u>
3894(02)00282-0

- 27. Pommerening, K., Rein, H., Bertram, D., Miiller, R., 1992. Estimation of dialdehyde groups in
 2.3-dialdehyde bead-cellulose, Carbohydr. Res. 233, 219-223. https://doi.org/10.1016/S00086215(00)90933-9
- 28. Raval, N.P., Shah, P.U., Shah, N.K. 2016. Adsorptive removal of nickel (II) ions from aqueous
 environment : a review. Journal of environmental management. 179, 1-20.
- 29. Salazar-Rabago, J.J., Leyva-Ramos, R., Rivera-Utrilla, J., Ocampo-Perez, R., Cerino-Cordova,
 F.J., 2017. Biosorption mechanism of Methylene Blue from aqueous solution onto White Pine
 (Pinus durangensis) sawdust: Effect of operating conditions. Sustain. Environ. Res. 27, 32–40.
 https://doi.org/10.1016/j.serj.2016.11.009
- 30. Semerjian, L., 2010. Equilibrium and kinetics of cadmium adsorption from aqueous
 solutions using untreated Pinus halepensis sawdust. J. Hazard. Mater. 173, 236–242.
 https://doi.org/10.1016/j.jhazmat.2009.08.074
- 31. Semerjian, L., 2018. Removal of heavy metals (Cu, Pb) from aqueous solutions using pine
 (Pinus halepensis) sawdust: Equilibrium, kinetic, and thermodynamic studies. Environ. Technol.
 Innov. 12, 91–103. https://doi.org/10.1016/j.eti.2018.08.005
- 32. Serencam, H., Gundogdu, A., Uygur, Y., Kemer, B., Bulut, V.N., Duran, C., Soylak, M., Tufekci,
 M., 2008. Removal of cadmium from aqueous solution by Nordmann fir (Abies nordmanniana
 (Stev.) Spach. Subsp. nordmanniana) leaves. Bioresour. Technol. 99, 1992–2000.
 https://doi.org/10.1016/j.biortech.2007.03.021
- Shukla, A., Zhang, Y.-H., Dubey, P., Margrave, J.L., Shukla, S.S., 2002. The role of sawdust in
 the removal of unwanted materials from water, J. Hazard. Mater. 95, 137-152.
 https://doi.org/10.1016/S0304-3894(02)00089-4
- 34. Shukla, S.S., Jia Yu, L., Dorris, K.L., Shukla, A., 2005. Removal of nickel from aqueous
 solutions by sawdust. J. Hazard. Mater. 121, 243-246.
 https://doi.org/10.1016/j.jhazmat.2004.11.025

35. St-Jean, A., Barguil, Y., Dominique, Y., Le Bot, B., Ayotte, P., Cordier, S., 2018. Nickel and
associated metals in New Caledonia: Exposure levels and their determinants. Environ Int. 118,
106-115. https://doi.org/10.1016/j.envint.2018.05.045

72636. Stuart, B., 2005. Infrared Spectroscopy, in: Kirk-Othmer Encyclopedia of Chemical727Technology. John Wiley & Sons, Inc., Hoboken, NJ, USA.728https://doi.org/10.1002/0471238961.0914061810151405.a01.pub2

- 37. Talibudeen, O., Greenland, D.J., 1981. The Chemistry of Soil Processes: Cation Exchange inSoils, Wiley, New York.
- 731 38. Torres, E. Biosorption: A Review of the Latest Advances. Processes. 2020. 8, 1584.
 732 https://doi.org/10.3390/pr8121584

39. Tran, H.N., You, S., Hosseini-Bandegharaei, A., Chao, H, 2017. Mistakes and inconsistencies
regarding adsorption of contaminants from aqueous solutions: A critical review. Water
Research. 120, 88-116.

- 40. Ucun, H., Kemal Bayhan, Y., Kayab, Y., Cakici, A., Algurb, F., 2003. Biosorption of lead (II)
 from aqueous solution by cone biomass of Pinus sylvestris. Desalination. 154, 233-238.
 https://doi.org/10.1016/S0011-9164(03)80038-3
- Varmat, A.J., Chavan, V.B., 1995. A study of crystallinity changes in oxidised celluloses.
 Polym. Degrad. Stab. 49 (2), 245-250. https://doi.org/10.1016/0141-3910(95)87006-7
- 42. Veglio, F., Beolchini, F., 1997. Removal of metals by biosorption: a review. Hydrometallurgy.
 44 (3), 301-316. https://doi.org/10.1016/S0304-386X(96)00059-X
- Vinícius, L., Gurgel, A., Karnitz, O., Nior, J., Pereira De Freitas Gil, R., Gil, L.F., 2007.
 Adsorption of Cu(II), Cd(II), and Pb(II) from aqueous single metal solutions by cellulose and
 mercerized cellulose chemically modified with succinic anhydride. Bioresour. Technol. 99 (8),
 3077-3083. https://doi.org/10.1016/j.biortech.2007.05.072
- Volesky, B., 2001. Detoxification of metal-bearing effluents: biosorption for the next
 century. Hydrometallurgy. 59 (2-3), 203-216. https://doi.org/10.1016/S0304-386X(00)00160-2.
- 45. Volesky, B., 2003. Biosorption process simulation tools. Hydrometallurgy. 71 (1-2), 179-190.
 https://doi.org/10.1016/S0304-386X(03)00155-5
- 46. Zeraatkar, A., Ahmadzadeh, H., Farhad Talebi, A., Moheimani, N. R., McHenry, M. P., 2016.
 Potential use of algae for heavy metal bioremediation, a critical review. J Environ Manage. 181,
 817-831. https://doi.org/10.1016/j.jenvman.2016.06.059
- 754

755 Figure Captions

756	Fig. 1. FTIR spectra of natural, treated and oxidized sawdust	8
757	Fig. 2. Characterizations by SEM of natural sawdust (a) at 1600x, treated SH+ (b), SF (c) at 650x	ć
758	and oxidized sawdust SCHO (d), SCOOH (e) at 650x	9
759	Fig. 3. Point of zero charge of natural sawdust, pH final against pH initial (a) and Δ pH against	
760	pH initial (b)1	0
761	Fig. 4. Effects of initial concentration of Ni ²⁺ and size of particles	.1
762	Fig. 5. Effect of adsorbent mass1	.2
763	Fig. 6. Effect of pH for the adsorption of 50 mg/L of Ni ²⁺ in sawdust (5g/L)1	.3

Fig. 7. Effect of contact time under basic (a, pH 8) or acidic (b, pH 4) conditions in 5g/L of	
adsorbent	. 14
Fig. 8. Curves fitting of non-linear Langmuir equation.	. 16
Fig. 9. Pseudo-second-order plot of Ni ²⁺ adsorption on P. caribaea sawdust.	. 18
Fig. 10. non-linear regression of Pseudo-second order in acid condition.	. 19
Fig. 11. Ni ²⁺ desorption efficiency of sawdust with HCl or H ₂ SO ₄ treatments.	. 19
Fig. 12. Ni ²⁺ adsorption on modified sawdust SH ⁺ (acidified), SCHO (di-aldehyde), SCOOH (2)	(di-
carboxylic), SCOOH (3) (tri-carboxylic) compared to natural sawdust and isolated cellulose	. 20
Fig. 13. Selectivity of metals (Ni ²⁺ , Mn ²⁺ , Co ²⁺ , Cr ³⁺) in natural versus Fenton oxidized sawdust	: in
a mixture of four metals (a) and separately (b) at 5.0 mg/L	. 22
Fig. 14. Reuse of natural pine sawdust for Ni2+ biosorption-desorption cycles (initial Ni2+	
concentration = 5.0 mg/L, sawdust concentration = 5.0 g/L, pH = 8, desorption solution: 10 n	۱L
of 0.1 HCl at 16 h)	. 23
	adsorbent. Fig. 8. Curves fitting of non-linear Langmuir equation. Fig. 9. Pseudo-second-order plot of Ni ²⁺ adsorption on P. caribaea sawdust. Fig. 10. non-linear regression of Pseudo-second order in acid condition. Fig. 11. Ni ²⁺ desorption efficiency of sawdust with HCl or H ₂ SO ₄ treatments. Fig. 12. Ni ²⁺ adsorption on modified sawdust SH ⁺ (acidified), SCHO (di-aldehyde), SCOOH (2) (carboxylic), SCOOH (3) (tri-carboxylic) compared to natural sawdust and isolated cellulose Fig. 13. Selectivity of metals (Ni ²⁺ , Mn ²⁺ , Co ²⁺ , Cr ³⁺) in natural versus Fenton oxidized sawdust a mixture of four metals (a) and separately (b) at 5.0 mg/L.

Tables:

779	Table 1 . Parameters of Langmuir isotherm models for Ni ²⁺ adsorption on P. caribaea sawdust,
780	comparison of linear and nonlinear models
781	Table 2. Parameters of Freundlich isotherm models for Ni2+ adsorption on P. caribaea sawdust,
782	comparison of linear and nonlinear models